Journal of the Taiwan Institute of Chemical Engineers 82 (2018) 156–162

Contents lists available at ScienceDirect

Journal of the Taiwan Institute of Chemical Engineers

journal homepage: www.elsevier.com/locate/jtice

Modeling and optimization of carbon dioxide methanation *via in situ* hydrogen generated from aluminum foil and alkaline water by Box–Behnken design

A.H. Zamani [a,*], Nor Hakimin Abdullah [b]

[a] Faculty of Industrial Sciences & Technology, Universiti Malaysia Pahang, 26300 Gambang, Kuantan, Pahang, Malaysia
[b] Advanced Materials Research Centre (AMRC), Faculty of Bioengineering and Tecnology, Universiti Malaysia Kelantan, 17600 Jeli, Kelantan, Malaysia

ARTICLE INFO

Article history:
Received 23 June 2017
Revised 8 November 2017
Accepted 10 November 2017
Available online 29 November 2017

Keywords:
Optimization
Response surface methodology
Green technology

ABSTRACT

The catalytic activity of carbon dioxide (CO_2) methanation by *in situ* hydrogen generated from aluminum foil (Al) and alkaline water over a novel catalyst (AHZ–CM) was investigated. Response surface methodology involving Box–Behnken design (RSM-BBD) was implemented for optimization where the reaction temperature was found to be the utmost significant effective factor, followed by H_2/CO_2 ratio and weight catalyst loading. The optimum condition for CO_2 conversion was at 3.29 g of weight catalyst loading, H_2/CO_2 ratio of 4.08 and reaction temperature of 276.7 °C which resulted in 97.5% of CO_2 conversion. The result was approximately in agreement with the predicted result found by RSM which achieved 99.9% CO_2 conversion. Interestingly, this study proved that the hydrogen gas production from Al and alkaline